



# META FRAC 20/40

UPG's **META FRAC 20/40** is a quality frac sand that is designed for standard well fracturing applications. **META FRAC** provides improved strength and conductivity at higher stress than other lower grade sands. **META FRAC 20/40** grade products are designed for closure stress up to 5,000 psi and temperatures up to at least 450°F.

UPG's **META FRAC** products provide excellent price / performance value, making it an economic alternative to low and medium density sands and a robust solution for use in wells where expensive ceramics or resins are out of budget and unnecessary. UPG's close proximity to your well head not only minimizes handling of our proppants but also reduces product cost so we can pass the saving on to you.

For more information about this product or to receive a sample please contact us at [info@unitedproppants.com](mailto:info@unitedproppants.com)

## Product Specifications

Roundness.....	6 of 10
Sphericity.....	8 of 10
Acid Solubility.....	2.8%
Turbidity (NTU).....	9.3
Bulk Density.....	98.1 lb/ft <sup>3</sup>
Median Particle Diameter.....	553
Specific Gravity.....	2.73 g/cc
Crush Resistance.....	5,000 PSI
K-Value.....	5K

Product Specifications are based upon API RP19C and ISO 13503-2 testing standards. UPG products professionally and independently tested by Stim-Labs & PropTesters.



[WWW.UNITEDPROPPANTS.COM](http://WWW.UNITEDPROPPANTS.COM)